

Kent Academic Repository

Hossain, Md. Moinul, Cugley, James, Lu, Gang, Smith, David, Kim, Ik Soo and Yan, Yong (2018) *Investigations into the Impact of Coal Moisture on Burner Performance through Flame Imaging and Spectroscopic Analysis.*In: 12th ECCRIA - The European Conference on Fuel and Energy Research and its Applications. . TFERF- The Fuel and Energy Research Forum (Unpublished)

Downloaded from

https://kar.kent.ac.uk/69029/ The University of Kent's Academic Repository KAR

The version of record is available from

This document version

Supplemental Material

DOI for this version

Licence for this version

UNSPECIFIED

Additional information

Versions of research works

Versions of Record

If this version is the version of record, it is the same as the published version available on the publisher's web site. Cite as the published version.

Author Accepted Manuscripts

If this document is identified as the Author Accepted Manuscript it is the version after peer review but before type setting, copy editing or publisher branding. Cite as Surname, Initial. (Year) 'Title of article'. To be published in *Title of Journal*, Volume and issue numbers [peer-reviewed accepted version]. Available at: DOI or URL (Accessed: date).

Enquiries

If you have questions about this document contact ResearchSupport@kent.ac.uk. Please include the URL of the record in KAR. If you believe that your, or a third party's rights have been compromised through this document please see our Take Down policy (available from https://www.kent.ac.uk/guides/kar-the-kent-academic-repository#policies).

Investigations into the Impact of Coal Moisture on Burner Performance through Flame Imaging and Spectroscopic Analysis

M. M. Hossain¹, J. Cugley¹, *G. Lu¹, D. Smith², I.S. Kim², Y. Yan¹

Despite increasing use of renewable energy worldwide, coal remains to be the primary energy resource to meet the increasing demand for electric power in many countries. However, coal-fired power plants have to cope with coals with different properties, including those with high moisture content. It is known that moisture content in coal does not only affect coal handling but also burner performance, and thus combustion efficiency and emission formation process. A study is recently carried out to investigate the impact of moisture content in coal on the burner performance through flame imaging and spectroscopic analysis. Experimental tests were conducted on a 40MW_{th} coal-fired combustion test facility (CTF). A typical pulverised coal was fired in the study. The variation in evaporated coal moisture was replicated by injecting steam into the primary coal flow in the range of 7%-55% (PFM, primary flow moisture) under different operation conditions including variations in furnace load and fuel-to-air ratio. A flame imaging system and a miniature spectrometer were employed to acquire concurrently flame images and spetroscopic data (Fig. 1). The characteristic parameters of the flame such as spreading angle, temperature, oscillation frequency and spectral intensity are computed and their relationship with the operation conditions including PFM and emissions (NO_x, CO) are quantified. Fig. 2 illustrates typical flame images under different steam injections. Detailed experimental results and analysis will be presented at the conference.




Fig. 1 Layout of flame monitoring systems

Fig. 2 Flame images

Keywords: CTF, high moisture coal, flame, digital imaging, image processing, spectroscopic analysis.

^{1.} School of Engineering and Digital Arts, University of Kent, Canterbury, Kent CT2 7NT, UK

² Doosan Babcock, Crawley Business Quarter, Manor Royal, Crawley, Sussex RH10 9AD, UK

^{*} Corresponding author: e-mail: g.lu@kent.ac.uk; tel: +44 1277823706, fax. +44 1277456084