

Kent Academic Repository

Yan, Xinggang, Spurgeon, Sarah K. and Edwards, Christopher (2017) *Mathematical Background*. In: Yan, Xinggang and Spurgeon, Sarah K. and Edwards, Christopher, eds. Variable Structure Control of Complex Systems: Analysis and Design. Communications and Control Engineering . Springer, pp. 27-41. ISBN 978-3-319-48961-2.

Downloaded from

https://kar.kent.ac.uk/69529/ The University of Kent's Academic Repository KAR

The version of record is available from

https://doi.org/10.1007/978-3-319-48962-9_2

This document version

Author's Accepted Manuscript

DOI for this version

Licence for this version UNSPECIFIED

Additional information

Versions of research works

Versions of Record

If this version is the version of record, it is the same as the published version available on the publisher's web site. Cite as the published version.

Author Accepted Manuscripts

If this document is identified as the Author Accepted Manuscript it is the version after peer review but before type setting, copy editing or publisher branding. Cite as Surname, Initial. (Year) 'Title of article'. To be published in *Title of Journal*, Volume and issue numbers [peer-reviewed accepted version]. Available at: DOI or URL (Accessed: date).

Enquiries

If you have questions about this document contact ResearchSupport@kent.ac.uk. Please include the URL of the record in KAR. If you believe that your, or a third party's rights have been compromised through this document please see our Take Down policy (available from https://www.kent.ac.uk/guides/kar-the-kent-academic-repository#policies).

Chapter 2

Mathematical Background

This Chapter presents some fundamental mathematical knowledge and basic results which facilitates the analysis and design in the subsequent chapters, and also helps readers understand the theoretical work presented in this book.

2.1 Lipschitz Function

This section will present the well known Lipschitz condition and the generalised Lipschitz condition.

2.1.1 Lipschitz Condition

The definition for Lipschitz condition is given as follows:

Definition 2.1. A function $f(x): \mathbb{R}^n \to \mathbb{R}^m$ is said to satisfy the *Lipschitz condition* in domain $\Omega \subset \mathbb{R}^n$ if there exists a nonnegative constant L such that the inequality

$$f(x) - f(\hat{x}) \le L||x - \hat{x}||$$
 (2.1)

holds for any $x \in \Omega$ and $\hat{x} \in \Omega$. Then L is called the *Lipschitz constant* and f(x) is called the *Lipschitz function* in Ω . If $\Omega = \mathbb{R}^n$, then f(x) is said to satisfy the *global Lipschitz condition*.

From the definition 2.1, it is clear to see that a Lipschitz function must be continuous. However the converse is not true and a typical example is the scalar function

$$f(x) = x^{1/3}$$

in a neighbourhood of the origin x = 0. A Lipschitz function may not be differentiable and a simple example is the scalar function

$$f(x) = |x|$$

at the origin x = 0 in $x \in \mathbb{R}$. Moreover, a differentiable function may not be Lipschitz on a compact set, for example the function

$$f(x) = \begin{cases} x^{\alpha} \sin \frac{1}{x}, & 0 < x \le 1 \\ 0, & x = 0 \end{cases}$$
 (2.2)

is not Lipschitz in the compact set $x \in [0, 1]$ for any constant α satisfying $1 < \alpha < 2$. The reason is that the derivative of the function f(x) defined in (2.2) is not bounded in the interval [0, 1].

Lemma 2.1. [97] Consider a function f(x): $\mathbb{R}^n \to \mathbb{R}^m$ which is differentiable in the domain Ω . If its' Jacobian matrix is bounded in Ω , that is, there exists a constant L such that

$$||J_f|| \leq L$$

for any $x \in \Omega$, then f(x) satisfies the Lipshitz condition, and the inequality (2.1) holds.

2.1.2 Generalised Lipschitz condition

The well known Lipschitz condition in Section 2.1.1 will be extended to a more general case which will be used in the analysis later.

Definition 2.2. A function $f(x_1,x_2,x_3): \Omega_1 \times \Omega_2 \times \Omega_3 \mapsto \mathbb{R}^n$ is said to satisfy a generalised Lipschitz condition with respect to (w.r.t.) the variables $x_1 \in \Omega_1 \subset \mathbb{R}^{n_1}$ and $x_2 \in \Omega_2 \subset \mathbb{R}^{n_2}$ uniformly for x_3 in $\Omega_3 \subset \mathbb{R}^{n_3}$ if there exist nonnegative continuous functions $\mathscr{L}_{f1}(\cdot)$ and $\mathscr{L}_{f2}(\cdot)$ defined in Ω_3 such that for any $\hat{x}_1, x_1 \in \Omega_1$ and $\hat{x}_2, x_2 \in \Omega_2$, the inequality

$$||f(x_1,x_2,x_3)-f(\hat{x}_1,\hat{x}_2,x_3)|| \le \mathcal{L}_{f_1}(x_3)||x_1-\hat{x}_1|| + \mathcal{L}_{f_2}(x_3)||x_2-\hat{x}_2||$$

holds for any $x_3 \in \Omega_3$. Then, $f(\cdot)$ is called a generalised Lipschitz function, and $\mathcal{L}_{f1}(\cdot)$ and $\mathcal{L}_{f2}(\cdot)$ are called generalised Lipschitz bounds. Further, if $\Omega_1 = \mathbb{R}^{n_1}$ and $\Omega_2 = \mathbb{R}^{n_2}$, then, it is said that $f(\cdot)$ satisfies a global generalised Lipschitz condition w.r.t. x_1 and x_2 uniformly for x_3 in Ω_3 .

Remark 2.1. The symbols $\mathcal{L}_{f1}(\cdot)$ and $\mathcal{L}_{f2}(\cdot)$ introduced above are usually nonnegative functions instead of constants. This is different from the Lipschitz condition. Thus, the nonnegative continuous functions $\mathcal{L}_{f1}(x_3)$ and $\mathcal{L}_{f2}(x_3)$ are called generalised Lipschitz bounds which are corresponding to the Lipschitz constant for the Lipschitz condition.

Clearly, the generalised Lipschitz condition is more relaxed than the Lipschitz condition. For example, the function

$$f(x_1,x_2,x_3) := x_1x_3^2 + x_2x_3$$

with $x_1, x_2, x_3 \in \mathbb{R}$ does not satisfy the global Lipschitz condition. However, from the inequality that for any $\operatorname{col}(x_1, x_2, x_3) \in \mathbb{R}^3$ and $\operatorname{col}(\hat{x}_1, \hat{x}_2, x_3) \in \mathbb{R}^3$

$$|f(x_1, x_2, x_3) - f(\hat{x}_1, \hat{x}_2, x_3)| \le |x_1 - \hat{x}_1|x_3^2 + |x_2 - \hat{x}_2| |x_3|$$

it clear to see that $f(\cdot)$ satisfies the global generalised Lipschitz condition w.r.t. x_1 and x_2 , uniformly for $x_3 \in \mathbb{R}$.

2.2 Comparison Functions

This section will present the definitions and properties of the class $\mathcal K$ function and the related functions.

Definition 2.3. (see [97]) A continuous function $\alpha: [0,a) \mapsto \mathbb{R}^+$ is said to belong to class \mathscr{K} if it is strictly increasing and $\alpha(0) = 0$. It is said to belong to class \mathscr{K}_{∞} if $a = \infty$ and $\lim_{r \to \infty} \alpha(r) = \infty$.

Definition 2.4. (see [97]) A continuous function $\beta:[0,a)\times\mathbb{R}^+\mapsto\mathbb{R}^+$ is said to belong to class \mathscr{KL} if, for any given $s\in\mathbb{R}^+$, the mapping $\beta(r,s)$ belongs to class \mathscr{K} with respect to the variable r, and for any given $r\in[0,a)$, the mapping $\beta(r,s)$ is decreasing with respect to the variable s and $\lim_{s\to\infty}\beta(r,s)=0$.

Definition 2.5. If a class \mathcal{K} function is a C^1 function, then it is said to belong to class $\mathcal{K}C^1$. A continuous function $\beta: \mathbb{R}^n \times \mathbb{R}^+ \mapsto \mathbb{R}^+$ is said to be a class $\mathcal{K}I$ function if for any given $x \in \mathbb{R}^n$ the function $\beta(x,s)$ is increasing with respect to the variable s in \mathbb{R}^+ , that is, $\beta(x,s_1) \leq \beta(x,s_2)$ for any $0 \leq s_1 \leq s_2$.

The functions defined in Definitions 2.3 and 2.4 above are directly from [97]. The new concepts of class $\mathcal{K}C^1$ function and class $\mathcal{K}I$ function are introduced in Definition 2.5 will be used for analysis later.

The following new concept is introduced, which will be termed a class $W\mathcal{S}$ function and will be used in Section 7.3.

Definition 2.6. A continuous function $\beta(t,x_1,x_2): \mathbb{R}^+ \times \mathbb{R}^+ \times \mathbb{R}^+ \mapsto \mathbb{R}^+$ (\mathbb{R}^+ is the set of nonnegative real numbers) with $\beta(t,0,0)=0$ is said to be weak w.r.t the variable x_1 and strong w.r.t. the variable x_2 if there exist functions $\chi_1(t,x_1,x_2)$ and $\chi_2(t,x_1,x_2)$ such that

$$\beta(t, x_1, x_2) = \chi_1(t, x_1, x_2)x_1 + \chi_2(t, x_1, x_2)x_2 \tag{2.3}$$

where both $\chi_1(\cdot,\cdot,x_2)$ and $\chi_2(\cdot,\cdot,x_2)$ are continuous and nondecreasing w.r.t. the variable x_2 . Further, the function $\beta(t,x_1,x_2)$ is said to be a class \mathscr{WS} function w.r.t. the variables x_1 and x_2 .

Remark 2.2. It should be noted that if a function $\beta(t,x_1,x_2): \mathbb{R}^+ \times \mathbb{R}^+ \times \mathbb{R}^+ \mapsto$ \mathbb{R}^+ with $\beta(t,0,0)=0$ is smooth enough, then it follows from [3] that there exist continuous functions $\beta_1(\cdot)$ and $\beta_2(\cdot)$ such that the expression

$$\beta(t, x_1, x_2) = \beta_1(t, x_1, x_2)x_1 + \beta_2(t, x_1, x_2)x_2$$

holds. Moreover, if $\beta_1(t,x_1,x_2)$ and $\beta_2(t,x_1,x_2)$ are nondecreasing w.r.t. x_2 , then $\beta(t, x_1, x_2)$ is a class \mathcal{WS} function w.r.t. x_1 and x_2 .

Lemma 2.2. (see [97]) Assume that $\alpha_1(\cdot)$ and $\alpha_2(\cdot)$ are class \mathcal{K} functions in [0, a), $\alpha_3(\cdot)$ and $\alpha_4(\cdot)$ are class \mathscr{K}_{∞} functions, and $\beta(\cdot)$ is a class $\mathscr{K}\mathscr{L}$ function defined in $[0, a) \times \mathbb{R}^+$. Then, the following results hold:

- the inverse function α₁⁻¹(·) is a class ℋ function defined in [0, α₁(a)).
 the inverse function α₃⁻¹(·) is a class ℋ_∞ function defined in [0, ∞).
- the composite function $\alpha_1 \circ \alpha_2$ is a class \mathcal{K} function.
- the composite function $\alpha_3 \circ \alpha_4$ is a class \mathcal{K}_{∞} function.
- the function $\sigma(r,s) = \alpha_1(\beta(\alpha_2(r),s))$ is a class \mathscr{KL} function.

Lemma 2.3. The following results hold:

- i) If $\beta(x,s): \mathbb{R}^n \times \mathbb{R}^+ \mapsto \mathbb{R}^+$ is a class $\mathscr{K}I$ function, then $\beta^2(x,s)$ is a class $\mathscr{K}I$ function.
- ii) Suppose that a function $\phi_1: [0,a) \mapsto \mathbb{R}^+$ is a C^1 function with $\phi_1(0) = 0$. Then there exists a continuous function $\phi_2(\cdot)$ in [0,a) such that

$$\phi_1(s) = \phi_2(s)s, \qquad s \in [0, a)$$

Proof: i) Suppose that $\beta(x,s): \mathbb{R}^n \times \mathbb{R}^+ \mapsto \mathbb{R}^+$ is a class $\mathscr{K}I$ function. Then for any $0 \le s_1 \le s_2$ and $x \in \mathbb{R}^n$,

$$\beta(x, s_1) \le \beta(x, s_2)$$

From $\beta(x,s) \ge 0$ for any $(x,s) \in \mathbb{R}^n \times \mathbb{R}^+$

$$\beta^{2}(x, s_{1}) - \beta^{2}(x, s_{2})$$

$$= (\beta(x, s_{1}) + \beta(x, s_{2}))(\beta(x, s_{1}) - \beta(x, s_{2}))$$

$$\leq 0$$

This shows that $\beta^2(x,s)$ is a class $\mathcal{K}I$ function

ii) Since the functions $\phi_1(\cdot)$ is a C^1 function in [0,a), its derivative $\frac{d\phi_1(s)}{ds}$ is continuous in [0,a). For any $s \in [0,a)$, construct a function

$$\phi_2(s) := \begin{cases} \frac{\phi_1(s)}{s}, & s \neq 0\\ \frac{d\phi_1(s)}{ds} \mid_{s=0}, s = 0 \end{cases}$$
 (2.4)

From the definition of $\phi_2(\cdot)$, it is clear to see that

1) if $s \neq 0$, then $\phi_1(s) = \phi_2(s)s$;

2) if
$$s = 0$$
, then from $\phi_1(0) = 0$, $\phi_1(s) = \phi_2(s)s$.

Therefore, the expression

$$\phi_1(s) = \phi_2(s)s$$

holds for $s \in [0,a)$. It remains to prove that the function $\phi_2(\cdot)$ defined in (2.4) is continuous in [0,a).

It is clear that $\phi_2(s)$ is continuous in (0,a). Since ϕ_1 is a C^1 function in [0,a), from the continuity of $\frac{d\phi_1(s)}{ds}$ at s=0,

$$\lim_{s \to 0^+} \phi_2(s) = \lim_{s \to 0^+} \frac{\phi_1(s)}{s} = \frac{d\phi_1(s)}{ds} \mid_{s=0} = \phi_2(0)$$

which implies that $\phi_2(\cdot)$ is continuous at s=0. Therefore $\phi_2(\cdot)$ is continuous in [0,a).

Hence the conclusion follows.

 ∇

2.3 Lyapunov Stability Theorems

The results given in this section are available in [97].

Consider the nonlinear system

$$\dot{x}(t) = f(t, x(t)) \tag{2.5}$$

where the function $f: \mathbb{R}^+ \times D \mapsto \mathbb{R}^n$ is continuous and $D \subset \mathbb{R}^n$ is a domain which contains the origin x = 0. It is assumed that

$$f(t,0) = 0, t \in \mathbb{R}^+$$

which implies that the origin is an equilibrium point of the system.

Definition 2.7. The equilibrium point x = 0 of system (2.5) is called exponential stable if there exist positive constants c_i for i = 1, 2, 3 such that for any $x(t_0)$ satisfying $||x(t_0)|| \le c_1$,

$$||x(t)|| \le c_2 ||x(t_0)|| e^{-c_3(t-t_0)}$$
 (2.6)

If inequality (2.6) holds for any $x(t_0) \in \mathbb{R}^n$, then, the equilibrium point x = 0 of system (2.5) is called globally exponentially stable.

2.3.1 Asymptotic stability

Theorem 2.1. Consider system (2.5). Let $V : \mathbb{R}^+ \times D \mapsto \mathbb{R}^+$ be a continuously differentiable function such that

$$W_1(x) \le V(t,x) \le W_2(x)$$

 $\frac{\partial V}{\partial t} + \frac{\partial V}{\partial x} f(t,x) \le -W_3(x)$

for any $t \in \mathbb{R}^+$ and $x \in D$, where $W_i(x)$ for i = 1,2,3 are continuously positive definite function in D. Then x = 0 is uniformly asymptotic stable. Further if $D = \mathbb{R}^n$, and w(x) is radially unbounded, then x = 0 is globally uniformly asymptotical stable.

2.3.2 Exponential stability

Theorem 2.2. Consider system (2.5). Let $V : \mathbb{R}^+ \times D \mapsto \mathbb{R}^+$ be a continuously differentiable function such that for $t \in \mathbb{R}^+$ and $x \in D$,

$$k_1 ||x||^a \le V(t, x) \le k_2 ||x||^a$$
$$\frac{\partial V}{\partial t} + \frac{\partial V}{\partial x} f(t, x) \le -k_3 ||x||^a$$

where k_i for i = 1,2,3 and a are positive constants. Then x = 0 is exponentially stable. Further if $D = \mathbb{R}^n$, then x = 0 is global exponentially stable.

Comparing Theorems 2.1 and 2.2 above, it is straightforward to see that the exponential stability implies uniform asymptotic stability.

2.3.3 Converse Lyapunov theorem

The following result is the well known Converse Lyapunov Theorem.

Theorem 2.3. Consider system (2.5) in domain $D := \mathcal{B}_r = \{x \in \mathbb{R}^n \mid ||x|| < r\}$. Let $\beta(\cdot)$ be a class \mathcal{KL} function and r_0 be a positive constant such that

$$\beta(r_0, 0) < r$$
 and $\mathscr{B}_{r_0} := \{x \mid ||x|| < r_0\}$

Assume that the Jacobian matrix $\frac{\partial f}{\partial x}$ is bounded¹ on domain D uniformly for $t \in \mathbb{R}^+$, and that the trajectory of system (2.5) satisfies

$$||x(t)|| \le \beta(||x(t_0)||, t-t_0), \qquad x(t_0) \in \mathcal{B}_{r_0}, \quad t \ge t_0 \ge 0$$

Then, there exists a continuously differentiable function $V : \mathbb{R}^+ \times \mathcal{B}_{r_0} \mapsto \mathbb{R}^+$ such that

¹ If the function $f(\cdot)$ in (2.5) is continuously differentiable in the ball $\overline{\mathscr{B}}_r$, then $\frac{\partial f}{\partial x}$ is bounded on the domain $D = \mathscr{B}_r$.

$$\alpha_{1}(\|x\|) \leq V(t,x) \leq \alpha_{2}(\|x\|)$$

$$\frac{\partial V}{\partial t} + \frac{\partial V}{\partial x} f(t,x) \leq -\alpha_{3}(\|x\|)$$

$$\left\| \frac{\partial V}{\partial x} \right\| \leq \alpha_{4}(\|x\|)$$

where α_i for i=1,2,3,4 are class \mathcal{K} functions defined on the interval $[0,r_0]$. The function $V(\cdot)$ can be chosen independent of time t if $f(\cdot)$ in system (2.5) is independent of the time t.

2.4 Uniformly Ultimate Boundedness

For a given system (2.5), if asymptotic stability is not possible, uniform ultimate bounded stability can be considered. This is very useful in practical cases.

Theorem 2.4. Consider system (2.5). Let $V : \mathbb{R}^+ \times D \mapsto \mathbb{R}^+$ be a continuously differentiable function such that in $t \in \mathbb{R}^+$ and $x \in \mathbb{R}^n$,

$$\begin{split} &\alpha_1(\|x\|) \leq V(t,x) \leq \alpha_2(\|x\|) \\ &\frac{\partial V}{\partial t} + \frac{\partial V}{\partial x} f(t,x) \leq -W_3(x), \quad \textit{for any} \quad \|x\| \geq \mu > 0 \end{split}$$

where $\alpha_1(\cdot)$ and $\alpha_2(\cdot)$ are class \mathcal{K} functions and $W_3(\cdot)$ is a continuous positive definite function in domain D. Then x=0 is uniformly ultimately bounded². Further if $D=\mathbb{R}^n$, and $\alpha_1(\cdot)$ belongs to class \mathcal{K}_{∞} , then x=0 is globally uniformly ultimately bounded.

Proof: See the reference [97] (Theorem 4.18, p. 172).

From Theorem 2.4, the following result is ready to be presented:

Lemma 2.4. Consider the nonlinear system

$$\dot{x} = \omega(x) \tag{2.7}$$

where $x \in \mathbb{R}^n$ is the system state, and the function $\omega(\cdot)$ is continuous in \mathbb{R}^n . Let $\mathscr{V} : \mathbb{R}^n \mapsto \mathbb{R}^+$ be a continuously differentiable class \mathscr{K}_{∞} function of ||x|| such that

$$\frac{\partial \mathcal{Y}}{\partial x}\omega(x) \le -\vartheta(\|x\|), \qquad x \in \mathbb{R}^n \setminus \mathscr{B}_{\nu}$$
 (2.8)

where ϑ is a class \mathcal{K} function, and μ is a positive constant. Then, the trajectory of system (2.7) enters into the domain \mathcal{B}_{μ} in finite time.

 $^{^2}$ The ultimate bound depends on the parameters μ , which can be estimated using the result given in Theorem 4.18 in [97].

Proof: From the condition of Lemma 2.4, there exists a class \mathscr{K}_{∞} function $\vartheta_1(\cdot)$ such that

$$\mathscr{V}(x) = \vartheta_1(\|x\|). \tag{2.9}$$

Then, from (2.8), (2.9) and using Theorem 2.4, the trajectory of system (2.7) is driven to the domain $\overline{\mathcal{B}}_{\mu}$ in a finite time, and remains there. That means there exists t_1 such that $x \in \overline{\mathcal{B}}_{\mu}$ for $t \ge t_1$.

The aim now is to prove that the trajectory of system (2.7) enters into \mathcal{B}_{μ} in a finite time. Suppose for a contradiction that this is not the case, then there exists some time t_2 such that the solution $x(x_0,t)$ of system (2.7) starting from some point x_0 satisfies $x(x_0,t) \in \partial \overline{\mathcal{B}}_{\mu}$ after t_2 . This is equivalent to

$$||x(x_0,t)|| = \mu,$$
 $t \ge t_2.$ (2.10)

By (2.9) and (2.10), it follows that

$$\mathcal{V}(x(x_0,t)) = \vartheta_1(\|x(x_0,t)\|) = \vartheta_1(\mu), \qquad t \ge t_2. \tag{2.11}$$

where μ is a positive constant. This shows that $\psi'|_{(2.7)} \equiv 0$ after t_2 , and it contradicts with (2.8). Hence, the conclusion follows.

Remark 2.3. Lemma 2.4 demonstrates that the solution enters the open set \mathscr{B}_{μ} in finite time and remains on $\overline{\mathscr{B}}_{\mu}$. It does not claim that the solution subsequently remains in \mathscr{B}_{μ} .

2.5 Razumikhin Theorem

Consider a time-delay system

$$\dot{x}(t) = f(t, x(t - d(t)))$$
 (2.12)

with an initial condition

$$x(t) = \phi(t), \qquad t \in [-\overline{d}, 0]$$

where the function vector $f: \mathbb{R}^+ \times \mathscr{C}_{[-\overline{d},0]} \mapsto \mathbb{R}^n$ takes $\mathbb{R} \times (\text{bounded sets of } \mathscr{C}_{[-\overline{d},0]})$ into bounded sets in \mathbb{R}^n ; d(t) > 0 is the time delay and

$$\overline{d} := \sup_{t \in \mathbb{R}^+} \{d(t)\} < \infty$$

which implies that the time delay d(t) has a finite upper bound in $t \in \mathbb{R}^+$.

Theorem 2.5. (Razumikhin Theorem) If there exist class \mathscr{K}_{∞} functions $\zeta_1(\cdot)$ and $\zeta_2(\cdot)$, a class \mathscr{K} function $\zeta_3(\cdot)$ and a continuous function $V_1(\cdot): [-\overline{d}, \infty] \times \mathbb{R}^n \mapsto \mathbb{R}^+$ satisfying

$$\zeta_1(||x||) \le V_1(t,x) \le \zeta_2(||x||), \quad t \in \mathbb{R}^+, \quad x \in \mathbb{R}^n$$

such that the time derivative of V_1 along the solution of system (2.12) satisfies

$$\dot{V}_1(t,x) \le -\zeta_3(\|x\|)$$
 if $V_1(t-d,x(t-d)) \le V_1(t,x(t))$ (2.13)

for any $d \in [0, \overline{d}]$, then the system (2.12) is uniformly stable. If in addition, $\zeta_3(\tau) > 0$ for $\tau > 0$ and there exists a continuous non-decreasing function $\xi(\tau) > \tau$ for $\tau > 0$ such that (2.13) is strengthened to

$$\dot{V}_1(t,x) \le -\zeta_3(\|x\|)$$
 if $V_1(t-d,x(t-d)) \le \xi(V_1(t,x(t)))$ (2.14)

for $d \in [0, \overline{d}]$, then the system (2.12) is uniformly asymptotic stable.

Proof: See pages 14-15 in [69].

 ∇

From Razumikhin Theorem 2.5. the following conclusion can be obtained directly:

Lemma 2.5. Consider the time delay system (2.12). If there exist constants $\gamma > 0$ and $\zeta > 1$ and a function

$$V_2(x(t)) = x^T \tilde{P} x$$

with $\tilde{P} > 0$ such that the time derivative of $V_2(\cdot)$ along the solution of system (2.12) satisfies

$$\dot{V}_2 \mid_{(2.12)} \le -\gamma \left\| \tilde{P}^{\frac{1}{2}} x(t) \right\|^2$$
 (2.15)

whenever

$$\|\tilde{P}^{\frac{1}{2}}x(t+\theta)\| \le \zeta \|\tilde{P}^{\frac{1}{2}}x(t)\|$$

for any $\theta \in [-\overline{d}, 0]$, then, system (2.12) is uniformly asymptotic stable.

Proof: From the definition of $V_2(\cdot)$ it follows that

$$\lambda_{\min}(\tilde{P})||x||^2 \le V_2(t,x(t)) \le \lambda_{\max}(\tilde{P})||x||^2$$

and from (2.15)

$$\dot{V}_2\mid_{(2.12)} \leq -\gamma x(t)^T \tilde{P} x(t) \leq -\gamma \lambda_{\max}(\tilde{P}) ||x||^2.$$

It is clear that the inequality

$$V_2(x(t+\theta)) < \zeta^2 V_2(x(t))$$

is equivalent to the inequality

$$\|\tilde{P}^{\frac{1}{2}}x(t+\theta)\| \le \zeta \|\tilde{P}^{\frac{1}{2}}x(t)\|$$

Then, from Razumikhin Theorem 2.5 and $\tilde{P} > 0$, the conclusion follows by letting

$$\begin{split} \gamma_1(\tau) &= \lambda_{\min}(\tilde{P})\tau^2, & \gamma_2(\tau) &= \lambda_{\max}(\tilde{P})\tau^2 \\ \gamma_3(\tau) &= \gamma\lambda_{\min}(\tilde{P})\tau^2, & \gamma_4(\tau) &= \zeta^2\tau \end{split}$$

in Theorem 2.5.

2.6 Output Sliding Surface Design

In order to form an output feedback sliding mode control scheme, it is usually required that the designed switching function is a function of system outputs. The corresponding sliding surface is called *an output sliding surface* in this book. The output sliding surface algorithm proposed in [39, 40] is outlined here, and this will be frequently used in the sequel.

Consider initially a linear system

$$\dot{x} = Ax + Bu \tag{2.16}$$

$$y = Cx, (2.17)$$

where $x \in \mathbb{R}^n$, $u \in \mathbb{R}^m$, $y \in \mathbb{R}^p$ are the states, inputs and outputs respectively and assume $m \le p < n$. The triple (A, B, C) comprises constant matrices of appropriate dimensions with B and C both being of full rank.

For system (2.16)-(2.17), it is assumed that

$$rank(CB) = m$$

Then, from [39] it can be shown that a coordinate transformation $\widetilde{x} = \widetilde{T}x$ exists such that the system triple (A,B,C) with respect to the new coordinate \widetilde{x} has the following structure

$$\begin{bmatrix} \widetilde{A}_{11} & \widetilde{A}_{12} \\ \widetilde{A}_{21} & \widetilde{A}_{22} \end{bmatrix}, \quad \begin{bmatrix} 0 \\ B_2 \end{bmatrix}, \quad \begin{bmatrix} 0 & \widecheck{T} \end{bmatrix}$$
 (2.18)

where $\widetilde{A}_{11} \in \mathbb{R}^{(n-m)\times (n-m)}$, $B_2 \in \mathbb{R}^{m\times m}$ and $\widecheck{T} \in \mathbb{R}^{p\times p}$ is orthogonal. Further, it is assumed that the system $(\widetilde{A}_{11}, \widetilde{A}_{12}, \widetilde{C}_1)$ with \widetilde{C}_1 defined by

$$\widetilde{C}_1 = \left[\begin{array}{c} 0_{(p-m)\times(n-m)} & I_{p-m} \end{array} \right] \tag{2.19}$$

is output feedback stabilisable i.e. there exists a matrix $K \in \mathbb{R}^{m \times (p-m)}$ such that

$$\widetilde{A}_{11} - \widetilde{A}_{12} K\widetilde{C}_1$$

is stable. It is shown in [39, 40] that a necessary condition for $(\widetilde{A}_{11}, \widetilde{A}_{12}, \widetilde{C}_1)$ to be stabilisable is that the invariant zeros of (A, B, C) lie in the open left half-plane. In [39, 40] a sliding surface of the form

$$FCx = 0 (2.20)$$

is proposed where

$$F = F_2 \left[K \quad I_m \right] \breve{T}^{\tau} \tag{2.21}$$

and $F_2 \in \mathbb{R}^{m \times m}$ is any nonsingular matrix.

If a further coordinate change is introduced based on the nonsingular transformation $z=\widehat{T}\widetilde{x}$ with \widehat{T} defined by

$$\widehat{T} = \begin{bmatrix} I_{n-m} & 0 \\ K\widetilde{C}_1 & I_m \end{bmatrix}$$

then in the new coordinates z, system (2.16)–(2.17) has the following form

$$\begin{bmatrix} A_{11} & A_{12} \\ A_{21} & A_{22} \end{bmatrix}, \qquad \begin{bmatrix} 0 \\ B_2 \end{bmatrix}, \qquad \widehat{C}$$

where $A_{11} = \widetilde{A}_{11} - \widetilde{A}_{12}K\widetilde{C}_1$ is stable and \widehat{C} satisfies

$$F\widehat{C} = \begin{bmatrix} 0 & F_2 \end{bmatrix}$$

with F_2 nonsingular. From the analysis above, the following conclusion is obtained directly:

Lemma 2.6. Consider system (2.16)-(2.17). Suppose that

- *i*) rank(CB) = m;
- ii) the invariant zeros of (A, B, C) lie in the open left half-plane;
- iii)the matrix triple $(\widetilde{A}_{11}, \widetilde{A}_{12}, \widetilde{C}_1)$ is output feedback stabilisable where $(\widetilde{A}_{11}, \widetilde{A}_{12})$ and \widetilde{C}_1 are defined respectively by (2.18) and (2.19).

Then,

i) there exists a transformation z = Tx such that in the new coordinate z system (2.16)–(2.17) has the following form

$$\dot{z} = \begin{bmatrix} A_{11} & A_{12} \\ A_{21} & A_{22} \end{bmatrix} z + \begin{bmatrix} 0 \\ B_2 \end{bmatrix} u \tag{2.22}$$

$$y = \begin{bmatrix} 0 & C_2 \end{bmatrix} z, \tag{2.23}$$

where $A_{11} \in \mathbb{R}^{(n-m)\times(n-m)}$ is stable. Both matrices $B_2 \in \mathbb{R}^{m\times m}$ and $C_2 \in \mathbb{R}^{p\times p}$ are nonsingular;

ii) there exists a matrix F such that FCx = 0 provides a stable sliding motion for system (2.16)-(2.17) and $F \begin{bmatrix} 0 & C_2 \end{bmatrix} = \begin{bmatrix} 0 & F_2 \end{bmatrix}$ where $F_2 \in \mathbb{R}^{m \times m}$ is nonsingular.

Proof: All that remains to be shown is that the output distribution matrix has the form given in (2.23) and that C_2 is nonsingular. The output distribution matrix in the new coordinates is given by

$$\begin{bmatrix} 0 & \breve{T} \end{bmatrix} \widehat{T}^{-1} = \begin{bmatrix} 0 & \breve{T} \end{bmatrix} \begin{bmatrix} I_{n-m} & 0 \\ -K\widetilde{C}_1 & I_m \end{bmatrix}$$

$$= \begin{bmatrix} 0 & \breve{T} \end{bmatrix} \begin{bmatrix} I_{n-p} & 0 & 0 \\ 0 & I_{p-m} & 0 \\ 0 & -K & I_m \end{bmatrix}$$

$$= \begin{bmatrix} 0 & \breve{T} \end{bmatrix} \begin{bmatrix} I_{n-m} & 0 \\ 0 & \begin{bmatrix} I_{p-m} & 0 \\ -K & I_m \end{bmatrix} \end{bmatrix}$$

$$= \begin{bmatrix} 0 & \breve{T} \begin{bmatrix} I_{p-m} & 0 \\ -K & I_m \end{bmatrix} \end{bmatrix}.$$

and so by inspection,

$$C_2 = \breve{T} \begin{bmatrix} I_{p-m} & 0 \\ -K & I_m \end{bmatrix}$$

which is nonsingular. Hence the result follows.

From the analysis above, it is clear to see that the coordinate transformation

$$z = Tx$$

where $T := \widehat{T}\widetilde{T}$, transfers the system (2.16)-(2.17) to the regular form (2.22)–(2.23). Choose the sliding surface

$$\mathcal{S} = \{ x \mid FCx = 0, \ x \in \mathbb{R}^n \} \tag{2.24}$$

Then, the analysis above shows that the sliding motion of system (2.16)-(2.17) corresponding to the sliding surface (2.24) is asymptotically stable. The sliding surface (2.24) can be described by

$$\mathscr{S} = \{ y \mid Fy = 0, \ y \in \mathbb{R}^p \}$$
 (2.25)

which is a subspace of the *output space*. Therefore $\mathcal S$ in (2.24) or (2.25) denotes *output sliding surfaces*.

Remark 2.4. Lemma 2.6 gives a condition for the existence of the output switching surface (2.20) on which system (2.16) is stable. It should be emphasized that the sliding surface given by Lemma 2.6 can be obtained from a systematic algorithm together with any output feedback pole placement algorithm of choice. Details of appropriate algorithms and how to determine the switching surface (2.20) is described in [39, 40] where the necessary and sufficient condition to guarantee the existence of the matrix F is available in Proposition 5.2 of [40]. If p = m then there is no design freedom and the sliding motion is governed by the invariant zeros of (A, B, C).

2.7 Geometric Structure of Nonlinear System

Consider the nonlinear system

$$\dot{x}(t) = F(x(t), u(t)) \tag{2.26}$$

$$y(t) = h(x(t)), x_0 = x(0) (2.27)$$

where $x \in \Omega \subset \mathcal{R}^n$ (and Ω is a neighbourhood of x_0), $u = \operatorname{col}(u_1, u_2, \dots, u_m) \in$ $\mathscr{U} \in \mathscr{R}^m$, and $y = \operatorname{col}(y_1, y_2, \dots, y_p) \in \mathscr{R}^p$ are the state variables, inputs and outputs respectively where \mathcal{U} is an admissible control set. F(x,u) is a known smooth vector field in $\Omega \times \mathcal{U}$ and the known function $h: \Omega \mapsto \mathcal{R}^p$ is smooth. For convenience, the system (2.26)–(2.27) is also denoted by the pair (F(x,u),h(x)).

Definition 2.8. (See, e.g. [62]) System (2.26)–(2.27) is said to be *observable* at $(x_0,u_0) \in \Omega \times \mathscr{U}$ if there exists a neighbourhood \mathscr{N} of (x_0,u_0) in $\Omega \times \mathscr{U}$ and a set of nonnegative integer numbers $\{r_1, r_2, \dots, r_p\}$ with $\sum_{i=1}^p r_i = n$ such that

1) for all $(x, u) \in \mathcal{N}$

$$\frac{\partial}{\partial u_i} L_{F(x,u)}^k h_i(x) = 0 \tag{2.28}$$

for indices $i=1,2,\ldots,p,$ $k=0,1,2,\ldots,r_i-1$ and $j=1,2,\ldots,m;$ 2) the $p\times m$ matrix $M(x,u):=\{\frac{\partial}{\partial u_j}L_{F(x,u)}^{r_i}h_i(x)\}$ has rank p in (x_0,u_0)

Then, $\{r_1, r_2, \dots, r_p\}$ is called the *observability index* of system (2.26)–(2.27) at (x_0, u_0) . Further, system (2.26)–(2.27) is said to be *uniformly observable* in $\Omega \times \mathcal{U}$ if for any $(x_0, u_0) \in \Omega \times \mathcal{U}$, the system is observable and the observability indices are fixed.

• Assume the pair (F(x,u),h(x)) has uniform observability index $\{r_1,r_2,\cdots,r_p\}$ with $\sum_{i=1}^{p} r_i = n$ in the domain $\Omega \times \mathcal{U}$.

Construct a nonlinear transformation $T: x \mapsto z$ as follows:

$$z_{i1} = h_i(x) \tag{2.29}$$

$$z_{i2} = L_{F(x,u)} h_i(x) (2.30)$$

$$\vdots
z_{ir_i} = L_{F(x,u)}^{r_i-1} h_i(x)$$
(2.31)

where $z_i := \text{col}(z_{i1}, z_{i2}, \dots, z_{ir_i})$ for $i = 1, 2, \dots, p$ and $z := \text{col}(z_1, z_2, \dots, z_p)$.

It follows from Definition 2.8 that M(x,u) has rank p in $\Omega \times \mathcal{U}$, implying that all z_i are independent of the control u, which combined with the restriction $\sum_{i=1}^p r_i = n$ means that the corresponding Jacobian matrix of T(x), $\frac{\partial T}{\partial x}$, is nonsingular. Therefore, (2.29)–(2.31) is a diffeomorphism in the domain Ω , and $z = \operatorname{col}(z_1, z_2, \ldots, z_p)$ forms a new coordinate system which can be obtained by direct computation from (2.29)-(2.31).

Since $L_{F(x,u)}^j h_i(x)$ is independent of u for all $i=1,2,\ldots,p$ and $j=1,2,\ldots,r_i-1$, it follows by direct computation that for $i=1,2,\ldots,p$

$$\begin{split} \dot{z}_{i1} &= \frac{\partial h_i}{\partial x} F(x, u) = L_{F(x, u)} h_i(x) = z_{i2} \\ \dot{z}_{i2} &= \frac{\partial \left(L_{F(x, u)} h_i(x)\right)}{\partial x} F(x, u) = L_{F(x, u)}^2 h_i(x) = z_{i3} \\ &\vdots \\ \dot{z}_{ir_{i-1}} &= L_{F(x, u)}^{r_i - 1} h_i(x) = z_{ir_i} \\ \dot{z}_{ir_i} &= L_{F(x, u)}^{r_i} h_i(x) \end{split}$$

Therefore, in the new coordinates z defined by (2.29)–(2.31), system (2.26)–(2.27) has the following form

$$\dot{z} = Az + B\Phi(z, u)$$
$$y = Cz$$

where

$$A = \operatorname{diag}\{A_1, \dots, A_p\}, \quad B = \operatorname{diag}\{B_1, \dots, B_p\} \quad \text{and} \quad C = \operatorname{diag}\{C_1, \dots, C_p\}$$

where $A_i \in \mathcal{R}^{r_i \times r_i}$, $B_i \in \mathcal{R}^{r_i \times 1}$ and $C_i \in \mathcal{R}^{1 \times r_i}$ for i = 1, 2, ..., p are defined by

$$A_{i} = \begin{bmatrix} 0 & 1 & 0 & \cdots & 0 \\ 0 & 0 & 1 & \cdots & 0 \\ \vdots & \vdots & \vdots & & \vdots \\ 0 & 0 & 0 & \cdots & 1 \\ 0 & 0 & 0 & \cdots & 0 \end{bmatrix}, \qquad B_{i} = \begin{bmatrix} 0 \\ 0 \\ \vdots \\ 0 \\ 1 \end{bmatrix}, \qquad C_{i} = \begin{bmatrix} 1 & 0 & \cdots & 0 \end{bmatrix}$$
(2.32)

and

$$\Phi(z,u) := \begin{bmatrix} \phi_{1}(z,u) \\ \phi_{2}(z,u) \\ \vdots \\ \phi_{p}(z,u) \end{bmatrix} := \begin{bmatrix} L_{F(x,u)}^{r_{1}}h_{1}(x) \\ L_{F(x,u)}^{r_{2}}h_{2}(x) \\ \vdots \\ L_{F(x,u)}^{r_{p}}h_{p}(x) \end{bmatrix}_{x=T^{-1}(z)}$$
(2.33)

where $\phi_i : T(\Omega) \times \mathcal{U} \mapsto \mathcal{R}$ for i = 1, 2, ..., p.

2.8 Summary 41

2.8 Summary

This chapter has presented the fundamental concepts and results which underpin the theoretical analysis in this book. Some of the results are from the existing work and the others are developed by the authors but with rigorous proof provided. The content covers Lipschitz condition, comparison functions, stability of nonlinear systems, the converse Lyapunov theorem and uniformly ultimate boundedness. The well known Razumikhin Theorem has been presented, for readers' convenience, which will be employed to deal with time delay throughout the book. Section 2.5 summarises the output sliding surface design approach proposed in [40] which will be frequently used in the sequel. Finally the geometric structure of nonlinear systems with uniform observability index has been provided.